



SPECIFICATIONS

PARAMETER	UNITS	
FERRULE ID	um	127
INSERTION LOSS	dB	≤ 0.2
DURABILITY (500 TIMES)	dB	≤ 0.3
OPERATING TEMPERATURE	°C	-20 ~ + 75
STORAGE TEMPERATURE	°C	-40 ~ + 85
TYPICAL CABLE OD	mm	∅ 2.0

XX = LENGTH (METERS)

01 - 1 METER	08 - 8 METER
02 - 2 METER	09 - 9 METER
03 - 3 METER	10 - 10 METER
04 - 4 METER	15 - 15 METER
05 - 5 METER	20 - 20 METER
06 - 6 METER	25 - 25 METER
07 - 7 METER	30 - 30 METER

FEATURES:

1. LC CONNECTORS ARE COMPLIANT TIA/EIA-640-10, LUCENT: 640-252-256.
2. PRODUCT QUALITY COMPLY WITH GR-326-CORE.
3. RoHS COMPLIANCE.



ALLEN TEL PRODUCTS, INC.
30 TV5 DRIVE, HENDERSON, NEVADA 89014

**GBLC2-D5-XX LC TO LC DUPLEX
MULTIMODE 50/125 850nm OM4
LASER-OPTIMIZED 10Gb**